1968 Corvette L88: ESL Bulletin: Front End Roll During Hard Cornering

Subject: Front End Roll During Hard Cornering **Model and Year:** 1968 Corvette with RPO L-88

Source: E.S.L. Bulletin **Bulletin No:** 963 (T.N.)

Date: 68-10-3

FRONT END ROLL DURING HARD CORNERING - 1968 Corvette

w/RPO L88 (#963) (T.N.)

It has come to our attention that the base production 327 type front stabilizer shaft could have been installed on some L88 equipped Corvettes built before 5-2-68. This installation can result in a reduction of front roll stiffness which may be noticeable to the more astute driver. In the event of a complaint of this nature, the front stabilizer shaft diameter should be measured. If the shaft measures 3/4" diameter instead of 15/16" diameter, then the following parts should be installed:

<u>QUANTITY</u>	<u>PART NO.</u>	<u>NAME</u>
1	3831972	Front Stabilizer Shaft (15/16" diameter)
2	3923674	Bushing

General Motors bulletins are intended for use by professional technicians, not a "do-it-yourselfer". They are written to inform those technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions and know-how to do a job properly and safely. If a condition is described, do not assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See a

General Motors dealer servicing your brand of General Motors vehicle for information on whether your vehicle may benefit from the information.

© Copyright General Motors Corporation. All Rights Reserved

Online URL:

https://www.corvetteactioncenter.com/tech/knowledgebase/article/1968-corvette-188-esl-bulletin-front-end-roll-during-hard-cornering-143.html