

1956 - 1968 Corvette: Service News: Connecting Rod Bolt Usage

Model Year: 1956-1968

Subject: Connecting Rod Bolt Usage

Source: Chevrolet Service News

Date: August, 1968

A new connecting rod assembly incorporating a 7/16" diameter connecting rod bolt is being used in late built Corvette R.P.O. L-88 (427 cu. in., 430 H.P.) engines and heavy duty M4 service engines. Early built R.P.O. L-88 engines and all other 427 cu. in. engines incorporate the 3/8" diameter bolt. The connecting rod nut used on the 7/16" diameter bolt should be torqued to 70 ft.-lbs.; the 3/8" diameter bolt nut should be torqued to 45 ft.-lbs.

Due to considerable variance between connecting rod bolt usages, a chart has been included in this article giving a listing of connecting rod applications by model year and by part number.

Connecting Rod Bolt Usage Chart		
Year	Application	
1968		
	Corvair	
	4 & 6 cylinder engines (except 292)	
	292 cu. in. engine	
	307, 327 & 350 cu. in. engine	
	366, 396, & 427 (except Corvette RPO L-88 2nd Design) cu. in. engine	

	Corvette RPO L-88 2nd Design (427 cu. in., 430 H.P.) ¹	
1967		
	Corvair	
	4 & 6 cylinder engines (except 292)	
	292 cu. in. engine	
	283, 327 & 350 cu. in engine	
	366, 396 & 427 cu. in. engine	
1963-1966		
	Corvair	
	4 & 6 cylinder (except 292 engine & 1963 L-6 engine used in K Series Trucks)	
	292 cu. in. engine	
	L6 engine used in 1963 K Series Trucks	
	V-8 engines (except 348, 409, 366, 396 & 427)	
	348 & 409 (except Special High Performance RPO Z-11)	
	Special High Performance 409 engine (RPO Z-11) offered in 1963	
	366, 396 & 427 cu. in. engine	
1962		
	Corvair	
	6 cylinder engines (except Chevy II)	
	Chevy II 4 & 6 cylinder engine	
	V-8 engines (except 348 & 409	

1956 ² -1961	engines)	
	348 & 409 cu. in. engine	
	Corvair	
	6 cylinder engines	
	V-8 engines (except 348 & 409 engines)	
	348 & 409 cu. in engine	
<p>1: Also used in Heavy Duty M4 service engines.</p> <p>2: For model years prior to 1956 reference Parts Catalog under 8</p>		

Connecting Rod Bolt Configuration		
Part No.	Thread	
3732718	3/8-24 x 2	
3789421	3/8-24 x 1 29/32	
3836670	3/8-24 x 2 1/4	
3837689	3/8-24 x 2 25/64	
38623720	3/8-24 x 2 1/8	
38923670	11/32-24 x 1 7/8	
3916399	3/8-24 x 1 39/64	
3942409	7/16-24 x 2 1/8	
6255636	5/16-24 x 1 57/64	

Online URL:

<https://www.corvetteactioncenter.com/tech/knowledgebase/article/1956-1968-corvette-service-news-connecting-rod-bolt-usage-686.html>