

1955 Corvette: Service Bulletin: Rear Engine Mountings 1955 Passenger 6 & 8 Cylinder With Powerglide

Model Year: 1955

Subject: Rear Engine Mountings 1955 Passenger 6 & 8 Cylinder with Powerglide

Source: Chevrolet Service Bulletin

Number: DR #230

Section: VI

Date: November 2, 1955

TO: ALL CHEVROLET DEALERS

In cases where the rear engine mounting bolts break or shear off on any 1955 Passenger Car with Powerglide Transmission, the 3/8" bolts and studs should be replaced with the special steel bolts and stud as listed below.

SERVICE

It will be necessary to remove the Powerglide Servo Cover and the Low and Drive Drive Valve Body to drill and tap the mounting holes in the Flywheel Housing for 7/16" - 14 stud and bolts, use drill Letter "U" which is .368" Diameter or a 23/64" Drill. It may also be necessary to drill the corresponding holes in the mounting to 7/16".

Flat Rate time two hours.

PARTS DATA

Required	Description	Part No.
1	Rear Mounting - Left Hand	3721665
1	Rear Mounting - Right Hand	3721666
3	Bolts (Special)	3722375

	Steel)	
4	Washers	120383
1	Nut	120370
1	Stud (Special Steel)	103215

Online URL:

<https://www.corvetteactioncenter.com/tech/knowledgebase/article/1955-corvette-service-bulletin-rear-engine-mountings-1955-passenger-6-8-cylinder-with-powerglide-772.html>